

# XMM-Newton CCF Release Note

XMM-CCF-REL-232

## EPIC MOS Fixed Offset Tables

M.J.S. Smith

August 8, 2007


### 1 CCF Components

Name of CCF	VALDATE	EVALDATE	Blocks Changed	CAL Version	XSCS Flag
EMOS1_DARKFRAME _0030.CCF	2007-08-01T06:00:00		OFFSET_CCD5		NO
EMOS2_DARKFRAME _0025.CCF	2007-07-12T05:12:03	2007-07-13T17:45:53	OFFSET_CCD1		NO
EMOS2_DARKFRAME _0026.CCF	2007-07-24T17:00:00	2007-07-25T18:00:00	OFFSET_CCD1		NO
EMOS2_DARKFRAME _0027.CCF	2007-08-01T06:00:00		OFFSET_CCD1 OFFSET_CCD2 OFFSET_CCD3 OFFSET_CCD6		NO

### 2 Changes

The OFFSET blocks in the DARKFRAME CCFs reflect the uploaded MOS fixed offset tables.

Analysis of MOS background maps shows a continued decrease in background for several MOS1 and MOS2 CCDs by  $\sim 1$  ADU per year. Periodically the uploaded MOS offset tables are revised so as to bring the offset in line with the background measured in the background maps. In this instance, the uploaded fixed column offsets for MOS1 CCD 5 and MOS2 CCDs 1 (FF mode), 2, 3 and 6 have been lowered by 1 ADU. Owing to re-planning of revolutions and manual commanding during observations there is a period of time in which the uploaded MOS fixed offset tables switch between previous and current versions. In some cases, commanding may affect the CCDs differently,



typically the central CCDs having differing offset tables with respect to the peripheral CCDs. This is reflected in this set of CCFs.

### 3 Scientific Impact and Estimated Quality

Lowering of the overall offset level for the CCDs mentioned above will restore the fixed offset to the level of the actual CCD offset. Too high offsets would result in the loss of events (or partial event charge) below threshold, whereas too low offsets would increase noise above threshold, potentially creating false events or adding charge to real events.

Note that the values in the OFFSET extensions of the DARKFRAME CCFs are *not* used to determine the E1 event energies; this is already done on board in the EDU. The main reason for reflecting the on board offset values in the DARKFRAME CCFs is correctly to determine the *reconstructed* event energies, for which knowledge of the contemporary on board offsets is required. Reconstructed event energies of 4095 ADU (so-called truncated events) can be useful in e.g. flare screening.

### 4 Expected Updates

The background of all CCDs changes in time and will need to be compensated through changes of the fixed offsets. These will have to be reflected in the OFFSET extensions of the DARKFRAME CCFs.

### 5 Test Procedures and Results

Correct functionality tested with `cifbuild` and `emproc` (SAS version 7.1.0). Reducing data with mismatched uploaded fixed offsets and DARKFRAME CCF issue may result in SAS warnings

```
** emevents: (spGatti11), reconstructed energy larger than 4095.
```

As expected, use of the CCFs in this release result in correct reconstructed energies and no such warnings are issued.